





Combining New Age Features with Classic Usability

Keeping up with the trend of Android mobile computers, CipherLab has been pushing boundaries to continuously update mobile data collection functions. As more users start to adopt the Android mobile computers, more features to satisfy various user behaviors are in higher demand. Crafted with operation-friendly designs, up-to-date features, powerful wireless options and versatile data capture functionality, the CipherLab RK25 mobile computer creates a perfect blend of new age features and classic usability to maximize your enterprise's usability.























Up-to-date Features for Big Volume Data Collection

As extensions from commercial smartphone, the RK25's Android operating system has a large display with management android apps that is easy to operate with simple numeric keypad. CipherLab's RK25 comes with 2 physical keypad designs for users to choose from. The physical buttons allow users to feel and press the buttons easily for faster data entry with higher accuracy, even during non-visual data entry applications which requires users to read off and simultaneously enter in data. Built for users in the retailing, light warehousing and field mobility industries, it fulfills the most diverse user behaviors in any environment with big volume data collection demands. The RK25 mobile computer effortlessly combines the benefits of touch computers with handheld terminals into one reliable device.



Big Display and Friendly Operation Design

With large and easy to use buttons, RK25 is made to best suit your specific preferences. Its 4" display with multi-touch panel has auto-adjustable backlight and sunlight visibility to ensure readability in all environments. Its 10 degree reading angle makes on-screen data checking simple by allowing users to read barcodes without laying the RK25 flat. Moreover, its compact 292 g, curved grip design reduces extended usage fatigue while delivering comfortable one-hand operation. Your staff will be able to extend their productivity to the fullest with RK25's friendly operation design.



Enterprise Usability with Updated Advancements

CipherLab RK25 is equipped with the latest quad-core 1.4 GHz processor and 2 GB RAM. Any complicated job process is immediately simplified with its high speed performance and smooth operation. Through its Micro SDHC card slot, the RK25's ample 16 GB memory is expandable to 32 GB so data-intensive applications can run smoothly. Android 7 Nougat with GMS certification allows the RK25 to meet enterprise security standards while supporting all Google official API including Google Play, G-mail and Google Map, significantly increasing your business' mobility.





Trustworthy Wi-Fi and Real-time Communication

The RK25's Wi-Fi transmission (IEEE802.11 a/b/g/n/ac) of dual band and fast roaming is the true definition of dependability in data-intensive environments such as warehouses. Furthermore, RK25's 4G/LTE can facilitate large file transmissions with high speed such as video streaming and remote access to back-end systems. Drive time is reduced with built-in GPS, GLONASS, Beidou and AGPS, providing the most accurate navigation. Communication among workers is kept at the most efficient level with instant voice connection, VoLTE with high definition voice or VoIP (PTT) with noise cancellation. With a simple touch of a button, instant communication between staffs is accomplished.

Durability to Support Harsh Environments

The CipherLab RK25's IP65, 1.5 m drop resistance and 300 tumbles at 0.5 m help support continuous work in rainy and dusty environment while fully protected against accidental drops. You don't have to worry about scratching the screen with the help of Corning Gorilla Glass 3. The keypad's numbers and letters have been inked with technology that won't fade with heavy usage. Moreover, it passed the durability test of one million keystrokes. On top of that, the 4000 mAh swappable battery keeps the durable productivity going for long shifts in any environment.



Resourceful Data Capture

CipherLab's RK25 offers reader versatility with linear imager, 2D imager and mid-range 2D imager, giving you long distance barcode reading capabilities over 4 m. Additionally, video and image capture is made simple with RK25's optional 8 MP camera. RK25's ability to support NFC applications of peer-to-peer and card emulation mode enables it to automate identification verification and eliminate the need of security key cards.



A Complete set of Utilities and Software

Compatible with various self-owned and 3rd party software, including SOTI and Wavelink(Ivanti), the RK25 provides simple device deployment and management.

With CipherLab Wireless Mobile Deployment System (WMDS), setup and synchronization is made easy. Users may efficiently deploy device configuration settings to a large number of devices. It also allows your staff to backup configuration with one click deployment, as well as duplicate device settings for different operating systems.

CipherLab Terminal Emulation supports systems of TN5250, TN3270 and VT100/102/220/ANSI with full screen operation for efficient inventory management. Your business will undoubtedly save time and energy with a full-screen operation where the intuitive user interface, Wi-Fi status, battery capacity, custom font size/color and more are available at your staff's disposal. Also, Button

Assignment speeds up the work process by allowing function key configuration.





CipherLab BarcodeToSetting creates user-friendly setup process, significantly shortening user's device setup time. Users may utilize Stage Tool to export certain configurations in the Android Development Configurator (ADC) and generate corresponding 1D/2D barcodes. With RK25's scans, all the required settings such as barcode reader, Wi-Fi, Terminal emulation, AppLock

and more, are done in a matter of seconds.







RK25



9	110000	MAAA	1101	-0 m n	LITOR
B.	lugged	MA(U) D			
	ساسا دا دانند				

	O conflict and the	And AND AND AND AND		
	Operating system	Android 7 Nougat with GMS		
	CPU	Qualcomm Quad-core 1.4 GHz		
	Memory	2GB RAM / 16GB Flash		
D. 6	Expansion	Micro SD card slot with SDHC support (up to 32GB)		
Performance	SIM / SAM	1 SIM slot and 1 optional SIM/SAM slot		
	Operating power	Replaceable and rechargeable 3.8V, 4000 mAh Li-Polymer battery		
	Working hours ¹	minimum 8 hours (2D imager)		
	Alert	Tri-color LEDs, vibrator, speaker		
	Interface supported	USB 2.0 OTG and charging contact		
Wireless	WWAN ²	GSM: Quad Band (850/900/1800/1900Mhz) TD-SCDMA: Band34, Band39 WCDMA: Band1, Band2, Band5, Band8 TDD-LTE: Band38, Band39, Band40, Band41 FDD-LTE: Band1, Band2, Band3, Band5, Band7, Band8, Band20		
communication	WLAN	IEEE 802.11 a/b/g/n/ac/d/h/i/k/r/e		
	WLAN security	WPA, WPA2, WEP, TKIP, AES, PEAP, TTLS, TLS, PWD, SIM		
	WPAN	Bluetooth® Class II, V4.0 BLE, V2.1 with Enhanced Data Rate (EDR)		
	Bluetooth® profile	GAP, SDP, HSP, SPP, GOEP, OPP, HFP, PAN, A2DP, AVRCP, GAVDP, HID, PBAP		
	GPS ³	GPS, Galileo, GLONASS, BeiDou, AGPS		
	Barcode scanning	Linear imager / 2D imager / Mid-Range 2D imager		
Data capture	RFID read / write (Optional)	HF RFID 13.56 MHz frequency which supports ISO14443 TYPE A,B, and ISO15693 Support NFC (Peer-to-Peer, Card Reader, Card Emulation)		
	Camera (Optional)	Autofocus 8 megapixels with LED flash		
	Display	4" WVGA 480 (W) x 800 (H), Corning Gorilla Glass 3, TN LCD		
	Touch panel	Capacitive touch with stylus, bare fingertip, and optional gloved fingertip inputs		
B	Interactive Sensor Technology	Accelerometer, Light sensor, proximity sensor, e-compass, Gyroscope		
Physical characteristics	Keypad	25-key/28-key numeric keypads with assignable keys, volume up and down keys, left and right trigger keys, power key		
Characteristics	Audio	Speaker, dual array microphones with echo and noise cancellation		
	Size (LxWxH)	168 x 73.8 x 26 mm		
	Weight	292 g (Mid-Range 2D imager with battery)		
	Operating temperature	-20°C to 50°C / -4°F to 122°F		
	Storage temperature	-30°C to 70°C / -22°F to 158°F		
	Humidity (non-condensed)	Operating 10% to 90% / Storage 5% to 95%		
User environment	Impact resistance	1.5 m (5 ft.) multiple drops onto concrete, 6 drops on each side, or 1.8 m (6 ft.) with rubber boot IP65 / 300 tumbles at 0.5 m		
	Electrostatic discharge	± 15 kV air discharge, ± 8 kV contact discharge		
	De sudete su consellence	CE, NCC, CCC, SRRC, ANATEL, BIS, WPC		
	Regulatory compliance	RoHS, REACH, WEEE, ErP, China RoHS		
Accessories	Standard	Hand strap, Charging and communication cradle, Charging and communication snap-on cable, Pistol grip, Rubber boot, Vehicle cradle, 4-slot battery charger		
	On request	Multi-slot Ethernet cradle, UHF RFID reader		
De	evelopment support	Android SDK, reader API, SAM API, HTML 5 API		
А	pplication software	CipherLab: Reader Configuration, Button Assignment, Wireless Mobile Deployment System (WMDS), Android Deployment Configurator (ADC) & BarcodeToSetting, Software Trigger Key, Terminal Emulation, App-Lock, Airlock Browser, Signature Capture, HF RFID Configuration Third party: SOTI (generic version), Wavelink (Ivanti), Xamarin Binding		
	Warranty	1 year		

- 1. Minimum 8 hours under WLAN and 2D scanning per 20 seconds, LCD 50% backlight and speaker on (volume is default) at 25°C, RFID off / Bluetooth® off / IEEE 802.11 a/b/g/n/ac on. The test is based on one broadcasting packet per second.
- 2. The mobile computer has received general telecommunication certification for data communication. Please check with your local carrier for the optimum operating efficiency.
- 3. GPS function is only available for WWAN models.





Charging and communication cradle



Charging and communication snap-on cable



Rubber boot



Vehicle cradle



Hand strap



Pistol grip



HEADQUARTERS CipherLab Co., Ltd. 12F, 333 Dunhua S. Rd., Sec.2 Taipei, Taiwan 10669 Tel +886 2 8647 1166 Fax +886 2 8732 3300 www.cipherlab.com

CipherLab Electronics Trading (Shanghai) Co., Ltd. J Room, 4F, No.728 West Yan'an Rd. Changning District, Shanghai China 200050 Tel +86 21 3368 0288 Toll Free 400 920 0285 Fax +86 21 3368 0286 CipherLab USA Inc. 2552 Summit Ave. STE 400 Plano, Texas, USA 75074 Tel +1 469 241 9779 Toll Free 888 300 9779 Fax +1 469 241 0697 CipherLab Europe Flight Forum 40, 5657 DB Eindhoven, The Nederlands Tel +31 40 295 1510